



RECOMMENDED PCB PATTERN DIM.
TOLERANCE : ± 0.05



- NOTES:
1.HOUSING: LCP HIGH-TEMP THERMOPLASTIC UL94V-0 COLOR:BLACK
2.TERMINAL/GROUND PLANE:PHOSPHOR BRONZE
PLATING:10u" GOLD IN CONTACT AREA, MATTE TIN ON TAIL.

30, c2 contacts	Dimensions			
	A.	B.	C.	D.
60	21.38	20.13	20.18	0.10
120	41.38	40.13	40.18	0.10
180	61.38	60.13	60.18	0.15
240	81.38	80.13	80.18	0.15
300	101.38	100.13	100.18	0.15

UNITS: mm		CSCONN		CSCONN PRECISE ELECTRONICS CO.,LTD	
GENERAL TOLERANCE		PART NO. (INTENDED USE)		TITLE:	
X. $\pm 5^\circ$	0. X ± 0.25	CBT-0550XXF-75		BTB 0.5MM XP FEMALE H=7.5MM	
X. $1 \pm 2^\circ$	0. XX ± 0.2	APPD:		DWG NO.	
XX. $\pm 1^\circ$	0. XXX ± 0.1	CHKD: Skila		BTB	
		DR: Kitty		SCALE	
				1:1	
				SHEET	
				1 OF 1	
				REV	
				A	

