



	A	B	C	D	E
30 PIN	11.2	12.5	14.2	16.2	16.8
40 PIN	15.2	16.5	18.2	20.2	20.8
50 PIN	19.2	20.5	22.2	24.2	24.8
60 PIN	23.2	24.5	26.2	28.2	28.8
70 PIN	27.2	28.5	30.2	32.2	32.8
80 PIN	31.2	32.5	34.2	36.2	36.8
90 PIN	35.2	36.5	38.2	40.2	40.8
100 PIN	39.2	40.5	42.2	44.2	44.8
110 PIN	43.2	44.5	46.2	48.2	48.8
120 PIN	47.2	48.5	50.2	52.2	52.8

Electrical:

- 1.Voltage: 50V AC(RMS)/DC
- 2.Current: 0.5A AC(RMS)/DC
- 3.Contact Resistance: 90 mΩ max
- 4.Withstanding Voltage:  
150V AC /RMS
- 5.Insulation Resistance: 500 MΩ min.
- 6.Operating Temperature:  $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$

Material:

Housing: High temperature Plastic(UL94V-0)  
Terminal:Copper Alloy

UNITS:		<b>CSCONN</b>	CSCONN PRECISE ELECTRONICS CO.,LTD			
GENERAL TOLERANCE			PART NO.(INTENDED USE)	TITLE: BTB 0.8MM XP MALE 浮动式		
X. ° ±5°	0. X ± 0.25	CBT-0860XXM-13	DWG NO. BTB			
X. 1 ± 2°	0. XX ± 0.2	APPD:	SCALE SHEET REV			
XX. ± 1°	0. XXX ± 0.1	CHKD: Skila		1:1	1 OF 1	A
		DR: Kitty				