

- NOTES: 1.
- 1.0 RATING.
 - 1.1 VOLTAGE: 100 VAC (GMS)
 - 1.2 CURRENT: 0.05 AMPERES MAX. PER CONTACT
 - 1.3 OPERATION TEMPERATURE RANGE: -25°C to +90°C
 - 2.0 ELECTRIC CHARACTERISTIC
 - 2.1 CONTACT RESISTANCE: 100mΩ MAX. MIN.
 - 2.2 INSULATION RESISTANCE: 1000MΩ
 - 2.3 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE
 - 3.0 OPERATION LIFE: 5000 CYCLES
 - 4.0 MATERIAL/FINISH: SEE TABLE A

ITEM	NAME	Q'TY/ EACH	MATERIAL/ FINISHED	REMARK
3	PAD	2	COPPER ALLOY SN PLATED	
2	CONTACT	8	COPPER ALLOY MATING AREA Au PLATED	
1	HOUSING	1	THERMOPLASTIC UL94V-0, BLACK	

CSCONN

CSCONN PRECISE ELECTRONICS CO., LTD

PART NO. (INTENDED USE)
CTR0812155001

APPD: SKI11a

CHKD: Kitty

DR: Kitty

UNITS: mm

GENERAL TOLERANCE

X ± 0.25

X.1 ± 0.2


X.1 ± 1°

APPD: SKI11a

CHKD: Kitty

DWG NO. T-FLASH CARD

TITLE: T-FLASH CARD 1.6H 抽屜式



SCALE	SHEET	REV
1:1	1 OF 1	A

RECOMMENDED PCB LAYOUT
TOLERANCES ±0.05