



pin number	pin name
G1	swlcth
pin 8	RSV
pin 7	DD
pin 6	VSS
pin 5	SCLK
pin 4	VDD
pin 3	DI
pin 2	CS
pin 1	RSV

P/N	DIM-A	DIM-H
CTF09115417003	0.70	1.70MM
CTF09115415003	0.50	1.50MM

**-NOTES-**

- 1.Electrical:  
 Contact resistance:50m ohms max.  
 Dielectric withstanding voltage:500V RMS.  
 Insulation resistance:1000M ohms min.
- 2.Mechanical:  
 MATE AND UNMATE FORCE:  
 MATE FORCE:4.5kg MAX  
 UNMATE FORCE:0.5kg MIN  
 Durability:1500cycles MIN.
- 3.Environment:  
 Operating Temperature:-25'to+85'.
- 4.FINISH:  
 TERMINAL: GOLD Plated Over NICKEL  
 Contact area,TIN ON  
 SOLDER TAIL AREA& TIN  
 Plated ALL Over NICKEL.  
 Shell: SPCC WITH NICKEL&GOLD Plated.
- 5.COLOR:  
 HOUSING:BLACK.

UNITS: mm		<b>CSCONN</b>	CSCONN PRECISE ELECTRONICS CO.,LTD			
GENERAL TOLERANCE			PART NO.(INTENDED USE)	TITLE:		
X. ° ±5°	0. X±0.25	CTF091154XX003	T-FLASH CARD 9P H=1.5/1.7MM短体			
X. 1 ±2°	0. XX±0.2	APPD:	DWG NO. TF CARD			
XX. ±1°	0. XXX±0.1	CHKD: Skila		SCALE	SHEET	REV
		DR: Kitty		1:1	1 OF 1	A